

MXD AGITATORS



- Highly corrosion resistant. Operable in severe operating environments. Comes standard in SUS 316 (other materials available)
- Simple mechanism facilitates maintenance
- Customisable to every application
- Operable at a wide range of sites ranging from water treatment through to manufacturing processes
- Highly adaptable
- Various optional



Model	Motor	Gear	RPM	Agitation shaft		Impellor	Max	Weight	Mount
	Ouput (kW)	Ratio		Length (mm)	Dia (mm)	dia (mm)	height (mm)	kg	type
M-10	0.37		900/6 PI	1000	16	140	1250	15	Flange
MG-10	0.75	10:1	280		25	350		22	Foot/FI
M-15	0.37		900/6 PI	1200	16	140	1500	15	Flange
MG-15	1.1	10:1	280		25	350	1800	22	Foot/FI
M-25	1.1		900/6 PI	1600	20		2000	17	Flange
MG-25	1.1	10:1	280		25	350		23	Foot/FI
MG-50	1.1			1800			25		
MG-100				2600			3000	28	

Optional:

- Variable Speed Drive
- Valves
- Agitators
- Automation systems
- Remote control systems
- pH/ Ec control
- Proportional dosing



agriplas



PERFECT WATER MANAGEMENT SOLUTIONS

CONTACT INFO:

PHONE: + 27 21 9135942
 CELL: + 27 83 4579991
 FAX: + 27 21 9135942
 e-mail: johan@irriquip.com